



# Volcano Wrap

**THERMAL CONTROL PRODUCTS, INC.**

**Volcano Wrap** is made from continuous filament basalt fiber and is engineered for protection from temperatures 1,200°F. When wrapped around exhaust pipes, the unique construction creates an attractive and durable finished product. It is very rugged and will not exhibit any vibration damage over long periods of use.

Sizes Available: 1" and 2" widths in 25' or 50' rolls



## Operating Temperatures

Test	Temperature
Max Continuous - MIL-I-23053	1200°F (649°C)
Melt Point - ASTM D-2117	2400°F (1316°C)

## Physical Properties

Flammability Rating	Non-flammable
Wall Thickness	.0625"
Color	Basalt
Recommended Cutting	Scissor



## Chemical Resistance

Aromatic Solvents	1
Aliphatic Solvents	1
Chlorinated Solvents	1
Weak Bases	1
Salts	1
Strong Bases	1
Salt Water - 0-S-1926	1
Hydraulic Fluid - MIL-H-5606	1
Lube Oil - MIL-L-7808	1
De-Icing Fluid - MIL-A-8243	1
Strong Acids	2
Strong Oxidants	2
Esters/Keytones	1
UV Light	2
Petroleum	1
Fungus - ASTM G-21	1

1=No Effect      2=Little Effect      3=Affected  
4=More Affected      5=Severely Affected

## FEATURES:

- High Temperature Resistance
- Easy To Install
- Resists Gasoline and Engine Chemicals
- Great Appearance

All statements herein are expressions of opinion that we believe to be accurate and reliable, but are presented without guaranty or responsibility on our part. Statements concerning possible use of our products are not intended as recommendations for their use alone or in combination with any materials or elements to infringe any patents. No patent warranty of any kind, express or implied, is made or intended.



6324 Performance Dr. • Concord, NC 28027

(p) 704.454.7605 • (f) 704.455.8931

www.thermalcontrolproducts.com